

LB-900 Mini Beacon



A versatile interior and general construction laser

Affordable, Versatile
and Easy to Use

One Person Operation

Indoor / Outdoor Use

Automatic Leveling

Off-Level Indicator

Built-in 90° Split Beam

One-Touch Reference
Point Positioning

Visible Chalkline

Auto / Manual
Operation for Slope

Optional Rechargeable
Ni-Cad Battery Pack


Low Battery Indicator



Interior applications for walls and ceilings



Site preparation in exterior applications



Built-in 90° Split Beam



One person setup using optional remote control



LB-900 Mini Beacon®

Specifications

Weight with Battery	5.2 lbs (2.3 kg)
Dimensions	6 x 6 x 7" (152 x 152 x 178 mm)
Operating Temperature	0° to 113°F (-18° to +45°C)
Storage Temperature	-40° to 149°F (-40° to +65°C)
Rotation Speeds	Slow, Medium, Fast
Scan Sweep Selections	0°, 10°, 45°, 90°, 180° (Approx.)
Self-leveling Range	± 5° (upright and laydown)
Accuracy	1/8" at 100' (3 mm at 30 m) at 70°F (20°C)*
Battery Operation	Up to 20 hours with alkaline**
Working Range	200 ft (60 m) diameter visual; 1000 ft (300 m) diameter with sensor 100 ft (30 m) plumb beam
Wavelength	635 nm
Laser Output	Maximum 3.0 mW rotating mode Maximum 1.0 mW stationary
Laser Class	Class II FDA / Class 2 IEC
Water Resistance	Water and dust resistant

* Accuracy is derated outside this temp range

** Battery life dependent upon environmental conditions

Illustrations, descriptions and technical data are not binding and may be changed.
 Printed in Switzerland. Copyright Leica Geosystems GR LLC, Michigan, USA, 2001.
 731019en - V.02 - RDU

Your dealer:



Laser class 2 in accordance with IEC 60825-1 and EN 60825-1
 Laser class II in accordance with FDA 21CFR Ch. I § 1040

Leica Geosystems GR LLC
 is an ISO 9001 Registered Company.

Leica
 Geosystems

Leica Geosystems GR LLC
 6330 28th Street SE
 Grand Rapids, Michigan 49546 USA
 Phone (616) 949-7430
 Fax (616) 949-6975
 www.laseralignment.com

